



### Frontloader KE 150 S

⊕	Volume	<b>150 litres</b>
⊙	Int. dimensions	<b>460 x 470 x 690 mm</b>
⊞	Power	<b>10.5 kW</b>
Ⓒ	Tanw *	<b>1290°C</b>

\* **Application temperature** for long-term and continuous use.

## Technical data

### ☰ Overview

Product group	<b>Kiln</b>
Design	<b>Frontloader</b>
Type	<b>KE-S series</b>

### ⏻ Energy

Energy type	<b>Electrical</b>
Power	<b>10.5 kW</b>
Supply	<b>16 A</b>
Voltage	<b>400V</b>
Connection	<b>CEE 16 A</b>


### ⊕ Dimensions

Volume	<b>150 litres</b>
Int. dimensions	<b>460 x 470 x 690 mm</b>
Ext. dimensions	<b>800 x 1050 x 1780 mm</b>
Weight	<b>363 kg</b>

### ☆ Equipment

Insulation	<b>3-layer</b>
Heating	<b>5-side</b>
Heating elements	<b>Support rods</b>
Control	<b>TC 304</b>

## Besondere Merkmale



### **Long-term application temperature Tapp 1290°C**

The kiln is designed for long-term and continuous use at temperatures up to 1290°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firing as well as high-temperature stoneware, soft paste porcelain firings. These applications correspond to Seger Cone 8 or Orton Cone 9.